



Application drainage profile

alferbal – The drainage profile with drip edge is suitable for laying tile and plate elements outdoors. Drainage slits ensure optimum drainage of stagnant water.

DESIGNED TO MEET THE SPECIAL REQUIREMENTS ON TERRACES AND BALCONIES.

Designed with ruggedness in mind, alferbal series defy any weather. Regardless of whether in new construction or for a subsequent renovation, the profiles protect the sensitive border areas effectively against rain and storms. The drainage profiles can drain the water and moisture quickly.

TECHNICAL SPECIFICATIONS

Alloy: EN AW 6060 (AlMgSi0,5)
Material number: 3.3206


All measures, weights and loads as indicated in this data sheet are approximate figures. We can not assume liability for any special applications as well as damage resulting from improper assembly or use, a corresponding suitability test must always be carried out by the customer.

INSTALLATION

Choose the drainage profile size according to the thickness of the tile. Align the profile, insert the drainage mat up to the profile. Adjust the installation bed thickness so that the tile edge matches the upper edge of the profile..

POWDER-COATED


ALUMINIUM



CORNER PIECE

POWDER-COATED


ALUMINIUM



CONNECTOR

POWDER-COATED

ALUMINIUM



DRAINAGE PROFILE AND ACCESSORIES MADE OF ALUMINIUM

DELIVERY FORM

The profiles are available in heights:
70; 90mm
depending on the surface (see catalog).

The profiles are available in lengths:
300 cm
depending on the surface (see catalog).

The accessories are available in heights:
70; 90mm
depending on the surface (see catalog).

SURFACES

Powdercoated

PACKING UNIT

Profiles
PU 1 = 10 pcs, PU 2 = 50 pcs, PU 3 = 150 pcs

Accessories
Blister = 1 pc

• PROCESSING, CARE, CLEANING

The following points must be observed in order to prevent damage on the profiles surfaces:

- Our processing instructions and the of the tile adhesive must always be observed.
- Any excess of grout, mortar and tile adhesive on the profile surface should be remove immediately with water.
- The protective film or similar, used for the installation, can only be removed after the Mortar setting completely.
- The profiles and accessories are cleaned with a damp cloth and pH-neutral cleaning agents. Please do not use alkaline products.

MATERIAL PROPERTIES

Aluminium drainage profiles and accessories can bear low to medium mechanical solicitations. The material has good corrosion resistance and a high tolerance and endurance to chemicals.

STORAGE AND TRANSPORT

The profiles and accessories must be protected against external and environmental threats.

DISPOSAL

The profiles and accessories can be delivered to authorized aluminium recycling centers.

SPECIAL NOTE

Warranty and disclaimer

The application examples and tips shown in this data sheet and on our website are guidelines based on conventional crafting techniques. All information, including product-related information is standard. The author excludes any warranty for the information given in the data sheet and on the website. For the usability of products for specific purposes and for the occurrence of damage or the occurrence of defects by the information or tips given here, no warranty is also accepted. Errors, misprints and technical changes - as far as they serve the progress - reserved. Photos and illustrations are not binding. No liability for printing and image defects. Imitation and reprinting, even in part, is not permitted.

As of: 06/2023