


# alferlight

LED SKIRTING BOARD  
MADE OF ALUMINIUM

# alferpro®



## Application LED skirting board

alferlight – When illuminated our decorative skirting boards are a real eye-catcher and will lead your way in the dark.


## LIGHTEN UP THE DARK AND ENSURE SAFETY IN A RELAXED ATMOSPHERE.

Light in the strict sense is not an element. Therefore, Light has a very strong impact on spacial effect. Today, LED technology allows almost unlimited freedom of design. Depending on the model, not only the brightness, but also the light colour can be smoothly controlled. The LED profiles are installed like classic tile profiles when laying the tiles in the covering. Cables and power supply are hidden under plaster or drywall.

## LED SKIRTING BOARD INCL. DIFFUSING DISC

ANODISED

ALUMINIUM



## TECHNICAL SPECIFICATIONS

AlMgSi0,5  
Material number: 33.206

All measures, weights and loads as indicated in this data sheet are approximate figures. We can not assume liability for any special applications as well as damage resulting from improper assembly or use, a corresponding suitability test must always be carried out by the customer.

## PROCESSING

Use a suitable adhesive or silicone to glue the skirting board onto the desired surface.

# alferlight

## LED SKIRTING BOARD MADE OF ALUMINIUM

alferpro®

### DELIVERY FORM

The profiles are available in the following heights:  
60 mm

The profiles are available in the following lengths:  
250 cm

The matching diffuser disc is included in the delivery.

### SURFACES

Brushed (240K)

### PACKING UNIT

PU 1 = 10 pcs, PU 2 = 50 pcs, PU 3 = 150 pcs

### PROCESSING, CARE, CLEANING

The profiles are cleaned with a damp cloth and pH-neutral cleaning agents. Please do not use alkaline products.

### MATERIAL PROPERTIES

Aluminium LED skirting boards are suitable on both indoor and outdoor areas and can bear low to medium mechanical solicitations. The material has good corrosion resistance and a high tolerance and endurance to chemicals.

### STORAGE AND TRANSPORT

The profiles must be protected against external and environmental threats.

### DISPOSAL

The profiles can be delivered to authorized aluminium recycling centers. The diffusing disc can be delivered to authorized plastic recycling centers.

### SPECIAL NOTE

#### Warranty and disclaimer

The application examples and tips shown in this data sheet and on our website are guidelines based on conventional crafting techniques. All information, including product-related information is standard. The author excludes any warranty for the information given in the data sheet and on the website. For the usability of products for specific purposes and for the occurrence of damage or the occurrence of defects by the information or tips given here, no warranty is also accepted. Errors, misprints and technical changes - as far as they serve the progress - reserved. Photos and illustrations are not binding. No liability for printing and image defects. Imitation and reprinting, even in part, is not permitted.

As of: 03/2021

alferpro®

Industriestrasse 7 · 79793 Wutoeschingen · Germany  
Tel +49 7746 92 01 500 · Fax +49 7746 92 01 85 00  
info.eng@alferpro.com · [www.alferpro.com](http://www.alferpro.com)

alferlight\_LED\_ASS\_A\_eng\_0321