

Application quarter circle profile

alfercircle – The closed quarter circle profile is suitable as a wall inside corner: robust protection for the tile edge and design element in one.

ROUNDED OUTER EDGES – VERY SAFE AND ELEGANT.

The symmetrical cross section of the alfercircle gives coverings a smooth transition or closure. Less prominent than the other series, alfercircle fades into the background, granting the lead role to the covering. The finish is completed with matching inner corners.

The discreetly rounded outer corners not only look great, they also reduce the risk of scratches in case of impact.

TECHNICAL SPECIFICATIONS


Polyvinyl chloride, hard
Short name PVC-U

All information is approximate. Since we can not assume liability for special applications, a corresponding suitability test must always be carried out by the customer.


PROCESSING

Choose the quarter circle profile according to the tile thickness. Apply the tile adhesive to the edge of the surface to be tiled with a notched trowel. Press in and align the quarter circle profile in the damp tile adhesive. Cover the attachment leg completely with glue. Press in and align the tile so that it matches the top of the profile.

PLASTIC



PLASTIC



QUARTER CIRCLE PROFILES AND ACCESSORIES MADE OF PLASTIC

DELIVERY FORM

The profiles are available in heights:
6; 8; 10; 11; 12,5mm
depending on the surface (see catalog).

The profiles are available in lengths:
250cm; 300 cm
depending on the surface (see catalog).

The accessories are available in heights:
6; 8; 10; 11; 12,5mm
depending on the surface (see catalog).

SURFACES

Matt, glossy

PACKING UNIT

Profiles
PU 1 = 10 pcs, PU 2 = 50 pcs, PU 3 = 150 pcs

Accessories
Blister = 2 pcs, ProPack = 30 pcs

PROCESSING, CARE, CLEANING

The following points must be observed in order to prevent damage on the profiles surfaces:

- The processing instructions of the tile adhesive must always be observed.
- Any excess of grout, mortar and tile adhesive on the profile surface should be removed immediately with water.
- Allow to dry out thoroughly, ensuring the area is well ventilated.
- The protective film or similar, used for the installation, can only be removed after the paving has dried completely.
- The profiles are cleaned with a damp cloth and pH-neutral agents.

MATERIAL PROPERTIES

Plastic quarter circle profiles and accessories are suitable for normal mechanical loads in indoor and outdoor areas and are partially resistant to chemicals. They are not UV resistant and fade over time. Avoid exposure to intense sunlight during storage.

STORAGE AND TRANSPORT

The profiles and accessories should be protected against external impact and abrasion.

DISPOSAL

The profiles and accessories can be supplied to plastic recycling.

SPECIAL NOTE

Warranty and disclaimer

The application examples and tips shown in this data sheet and on our website are guidelines based on conventional crafting techniques. All information, including product-related information is standard. The author excludes any warranty for the information given in the data sheet and on the website. For the usability of products for specific purposes and for the occurrence of damage or the occurrence of defects by the information or tips given here, no warranty is also accepted. Errors, misprints and technical changes - as far as they serve the progress - reserved. Photos and illustrations are not binding. No liability for printing and image defects. Imitation and reprinting, even in part, is not permitted.

As of: 05/2020