


# alferflex

EXPANSION JOINT PROFILE  
THICK BED MADE OF PLASTIC

# alferpro®



## Application expansion joint profile


alferflex – The expansion joint profiles were designed for laying with very high mechanical loads and provide lasting protection against stress cracking.

## DISCREET APPEARANCE DESPITE STRONG EFFECT. LAMINATE EXPANSION JOINTS WITH ALFERPRO PROFILES.

Expansion joints are for compensating floor tensions in large areas, especially in public or commercial spaces and alferflex is a functional solution which prevents cracks in the flooring. In order to keep the continuous appearance of a surface with as little disturbance as possible, we have designed very slim expansion joint profiles.

DARKGREY

PLASTIC



## TECHNICAL SPECIFICATIONS

Polyvinyl chloride, hard  
Short name PVC-U

All measures, weights and loads as indicated in this data sheet are approximate figures. We can not assume liability for any special applications as well as damage resulting from improper assembly or use, a corresponding suitability test must always be carried out by the customer.

## INSTALLATION

Choose the expansion joint profile according to the floor height. Press the profile (if necessary with anchors) into the mortar and align so that the upper edge of the profile matches the surface. Then fill in the joint between profile and tile with grout.

### DELIVERY FORM

The profiles are available in heights:  
30 mm  
depending on the surface (see catalog).

The profiles are available in lengths:  
250 cm  
depending on the surface (see catalog).

Joint width: 8 mm

### SURFACES

Matt

### PACKING UNIT

PU 1 = 10 pcs, PU 2 = 50 pcs, PU 3 = 150 pcs

### PROCESSING, CARE, CLEANING

The following points must be observed in order to prevent damage on the profiles surfaces:

- The processing instructions of the tile adhesive must always be observed.
- Any excess of grout, mortar and tile adhesive on the profile surface should be removed immediately with water.
- Allow to dry out thoroughly, ensuring the area is well ventilated.
- The protective film or similar, used for the installation, can only be removed after the paving has dried completely.
- The profiles are cleaned with a damp cloth and pH-neutral cleaning agents. Stubborn dirt on the profiles can also be removed with solvents. Please do not use aggressive cleaning agents for the silicone joint.

### MATERIAL PROPERTIES

Plastic expansion joint profiles are suitable on both indoor and outdoor areas and can bear normal mechanical solicitations. The material has a fair tolerance and endurance to chemicals. They are not UV resistant and fade over time. Avoid exposure to intense sunlight during storage.

### STORAGE AND TRANSPORT

The profiles must be protected against external and environmental threats.

### DISPOSAL

The profiles can be delivered to authorized plastic recycling centers.

### SPECIAL NOTE

#### Warranty and disclaimer

The application examples and tips shown in this data sheet and on our website are guidelines based on conventional crafting techniques. All information, including product-related information is standard. The author excludes any warranty for the information given in the data sheet and on the website. For the usability of products for specific purposes and for the occurrence of damage or the occurrence of defects by the information or tips given here, no warranty is also accepted. Errors, misprints and technical changes - as far as they serve the progress - reserved. Photos and illustrations are not binding. No liability for printing and image defects. Imitation and reprinting, even in part, is not permitted.

As of: 05/2020