



### SEALING – ISOLATING – DRAINING

Sealing membranes, decoupling mats and system components from alferground are ideally matched for the reliable sealing of damp and wet rooms - indoors, outdoors and with underfloor heating.

### TECHNICAL SPECIFICATIONS

Material: PP/PE, fleece-laminated, thermoplastic elastomer  
TPE, fabric-reinforced  
Colour: magenta

All information is approximate. Since we can not assume liability for special applications, a corresponding suitability test must always be carried out by the customer.


### PROCESSING

The sealing membrane and the sealing tapes, as well as the system parts, must be cut to the appropriate size and adjusted before installation begins.






In a first step, the outer and inner corners are glued to the prepared substrate and then the sealing tapes are glued to the joints in the floor/wall transition and in the area of the wall corners. The overlap is at least 5 cm. Penetrations and installation parts are sealed with the corresponding wall sleeves.

### MAGENTA

#### PLASTIC (TPE)



#### PLASTIC (PP/PE)



### DELIVERY FORM

- Sealing tape, fabric-reinforced
- Sealing tape: 12 cm width x 25 m length
- 12 cm width x 50 m length
- Inside corner: 14 cm wide
- Outer corner: 14 cm wide
- Wall sleeve: 12 cm wide
- Expansion zone sleeve: 14 cm wide

### PACKING UNIT

- Sealing tape:  
Piece = 1 roll, pallet = 50 rolls  
Piece = 1 roll, pallet = 120 rolls
- Inside corner:  
PU 1 = 1 piece, PU 2 = 25 pieces
- Outside corner:  
PU 1 = 1 piece, PU 2 = 25 pieces
- Wall sleeve:  
PU 1 = 1 piece, PU 2 = 25 pieces
- Expansion zone sleeve:  
PU 1 = 1 piece, PU 2 = 10 pieces

### SCOPE OF APPLICATION

Suitable for installation in damp and wet rooms indoors and outdoors. Processing within 24 months from the date of dispatch.

### SPECIFICATIONS

- Ready-to-lay welded moulded parts
- Quick and easy processing
- Maximum installation safety
- Ideal for renovation projects
- Suitable for underfloor heating

### STORAGE AND TRANSPORT

The system parts should be protected from impact and abrasion. Store at room temperature in a dry place, protected from direct sunlight.

### DISPOSAL

The system parts can be supplied to plastic recycling.

### SPECIAL NOTE

#### Warranty and disclaimer

The application examples and tips shown in this data sheet and on our website are guidelines based on conventional crafting techniques. All information, including product-related information is standard. The author excludes any warranty for the information given in the data sheet and on the website. For the usability of products for specific purposes and for the occurrence of damage or the occurrence of defects by the information or tips given here, no warranty is also accepted. Errors, misprints and technical changes - as far as they serve the progress - reserved. Photos and illustrations are not binding. No liability for printing and image defects. Imitation and reprinting, even in part, is not permitted.

As of: 03/2024